



CRBF/CRBE	Boundary dimensions						
	D	d	B	M	r <sub>min</sub>	OA	HA
1008	52	10	8	8	0.6	4-M3x0.5P	6-Ø3.4 through
							Ø6.5 counter bore depth 3.3
2012	70	20	12	12	0.6	6-M3x0.5P	6-Ø3.4 through
							Ø6.5 counter bore depth 3.3
2512	80	25	12	12	0.7	6-M3x0.5P	6-Ø3.4 through
							Ø6.5 counter bore depth 3.3
3515	95	35	15	15	0.9	8-M4x0.7P	8-Ø4.5 through
							Ø8 counter bore depth 4.4
5515	120	55	15	15	0.9	8-M5x0.8P	8-Ø5.5 through
							Ø9.5 counter bore depth 5.4
8022	165	80	22	22	1.4	10-M5x0.8P	10-Ø5.5 through
							Ø9.5 counter bore depth 5.4
9025	210	90	25	25	1.8	12-M8x1.25P	12-Ø9 through
							Ø14 counter bore depth 11

CRBF/CRBE	Boundary dimensions		Mass	Dynamic load rating	Static load rating
	V1 (PCD)	V2 (PCD)	( Kg)	C(N)	C(N)
1008	16	42	0.12	3400	3000
2012	28	57	0.31	7000	7400
2512	35	67	0.4	8000	9300
3515	45	83	0.66	14900	16700
5515	65	105	0.96	17400	22500
8022	97	148	2.6	34100	49000
9025	112	187	4.67	40700	56400

**Note\*:** If you need any others size or specification, please do not hesitate to contact *PMI*.