



Model No.	Bolt Size	
	S <sub>1</sub>	S <sub>2</sub>
MISG 17	M4	M3
MISG 21	M5	M4
MISG 27	M6	M5
MISG 35	M8	M6

Model No.	External dimension					Carriage dimension										
	Height H	Width W	Length L	$W_2$	$H_2$	B	C	F	$S \times l$	$L_1$	T	N	G	K	$d_1$	Grease Nipple
<b>MSG17 E</b>	17	60	50.2	13.5	2.5	53	26	18	M4x6	33.6	4.7	4.15	4	2.5	2.4	G-M3
MSG21 E	21	68	59	15.5	3	60	29	22	M5x8	40	6	5	12	5.5	2.5	G-M6
<b>MSG27 E</b>	27	80	72.2	19	3	70	40	24	M6x10	51.8	8	6	12	6.2	3.3	G-M6
MSG35 E	35	120	105.2	25.5	4	107	60	40	M8x14	77.6	11.42	7	12	8.55	3.3	G-M6

**Note:** The basic dynamic load rating C of ball type is based on the 50 km for nominal life. The conversion between C for 50 km and  $C_{100}$  for 100 km is  $C=1.26 \times C_{100}$ .

**Note\*:** Single: Single carriage/ Double: Double carriages closely contacting with each other.

Unit: mm

Model No.	Rail dimension					Basic load rating		Static moment rating				Weight		
	Width $W_1$	Height $H_1$	Pitch $P$	E std.	D × h × d	Dynamic C kN	Static $C_o$ kN	$M_p$ kN-m		$M_y$ kN-m		$M_R$ kN-m	Carriage kg	Rail kg/m
								Single*	Double*	Single*	Double*			
<b>MSG17 E</b>	33	9	40	15	7.5×5.3×4.5	4.8	8.6	0.05	0.24	0.05	0.24	0.14	0.14	2.02
MSG21 E	37	11	50	15	7.5×5.3×4.5	7	12.1	0.08	0.46	0.08	0.46	0.22	0.25	2.86
<b>MSG27 E</b>	42	15	60	20	7.5×5.3×4.5	12.4	20.2	0.15	0.87	0.15	0.87	0.42	0.31	4.49
MSG35 E	69	19	80	20	11×9×7	30.7	48.6	0.65	3.6	0.65	3.6	1.67	0.99	9.4