



単位:mm

品番	軸外径		循環 巻数	基本定格荷重(kgf)		ねじ寸法				ねじ寸法			ナット		フランジ					油穴		貫通穴		
	外径 d1	リード		動定格荷重 (1×10 <sup>6</sup> REV.) Ca	静定格荷重 Co	L1	L2	L3	L4	L5	L6	d2	Dg6	L	A	T	W	E	F	C	Q	X	Y	Z
PTR1205T3C7S-0300	12	5	3	420	720	240	60	300	15	180	7	12	30	32	50	10	40	45	32	15	M6	4.5	8	4.4
PTR1205T3C7S-0450						390		450																
PTR1210T3C7S-0600	12	10	3	420	720	540	60	600	15	180	7	12	30	45	50	10	40	45	32	15	M6	4.5	8	4.4
PTR1220T2C7S-0600	12	20	2	290	460	540	60	600	15	180	7	12	30	54	50	12	40	45	32	15	M6	4.5	8	4.4
PTR1505T3C7S-0600	15	5	3	750	1360	540	60	600	15	230	7	15	34	35	55	11	45	50	34	18	M6	5.5	9.5	5.4
PTR1510T3C7S-0450	15	10	3	750	1360	390	60	450	15	230	7	15	34	47	55	10	45	50	34	18	M6	5.5	9.5	5.4
PTR1510T3C7S-0600						540		600																
PTR1510T3C7S-0750						690		750																
PTR1510T3C7S-0900						840		900																
PTR1510T3C7S-1000						940		1000																
PTR1510T3C7S-1100						1040		1100																
PTR1510T3C7S-1300						1240		1300																
PTR1520T2C7S-0600						15		20																
PTR1520T2C7S-0750	690	750																						
PTR1520T2C7S-0900	840	900																						
PTR1520T2C7S-1000	940	1000																						
PTR1520T2C7S-1100	1040	1100																						
PTR1520T2C7S-1300	1240	1300																						
PTR2005T3C7S-0600	20	5	3	910	1930		520		80	600	15	230	7	20	44	35	67	11	55	60	44	22	M6	5.5
PTR2010T3C7S-0600	20	10	3	1210	2380	515	85	600	15	230	8	20	46	52	74	13	59	66	46	24	M6	6.6	11	6.5
PTR2010T3C7S-1000						915		1000																
PTR2010T3C7S-1500						1415		1500																